



## Flooring Specifications

# Reclaimed WHITE Oak - Remilled

<b>Species</b>	Quercus Alba (ALL white oak)
<b>Hardness</b>	Janka 1290 - 1360
<b>Thickness</b>	3/4" Solid, 5/8" Engineered w/4mm, 3/4" Engineered w/4mm OR 6mm
<b>Coloration</b>	Light reddish tan to medium brown natural color variation with occasional mineral and ferrous metal stain
<b>Grade Characteristics</b>	Natural medium to bold grain variation, tight or star cracked knots, minor checks and cracks to 1/8" on plank face, light to medium worm hole content, few to moderate nail holes and occasional fillable holes or voids to 3/4"
<b>Widths</b>	Available 3"-10", limited quantities 11" & wider RW(3"-5"), RW(3"-6"), RW(4"-7"), RW(5"-8") standard
<b>Lengths</b>	2' to 10'
<b>Moisture Content</b>	6%-9% at production
<b>Millwork</b>	Milled from planks re-sawn from reclaimed timbers with offset floor-matched tongue and groove, back-relieved End matching available to 10"
<b>Packaging</b>	Hand carry bundles of 4 boards high, 8'-10' long, securely strapped to wood skid of 36"-48" wide x 10'-12' long, weighs 2.6 - 3.1lbs/square foot
<b>Eco Status</b>	LEED MRc3 Eligible - 100% Reclaimed